

STR101P-HD-BS

Features:

- >1pc STR101P-HD-B1 + 1pc STR101P-S2
- >No power required, simplified project wiring
- >Compatible with HDCV1/ HDTV1/ AHD
- >Transmission distance (over Cat 5E/6):
 - HDCV1 720P/400m; 1080P/250m
 - HDTV1 720P&1080P/250m
 - AHD 720P/350m; 1080P/200m
- >Plug and play, real-time transmit CCTV HD video signal, video is high quality and stable
- >Anti-interference, super lighting protection, ESD
- >ABS outer shell, convenient to use in intensive project
- >1pc STR101P-HD-S2 push-terminal with pigtail, easier for installation, with connecting slot, many baluns can connect together
- >1pc STR101P-HD-B1 water-proof on the camera side



Video Balun
HD UTP

Specifications:

Category Type: UTP CAT5/ 5E/ 6
Twisted-pair Video Connector: BNC-M
Compatible Format: HDCVI/HDTV1/AHD
Resolution: 720P/1080P
Ant-interference: >60db

ESD:
 >1a contact discharge electricity level3
 >1b air discharge electricity level3
 >Per: IEC61000-4-2

Coaxial Cable Connector: 2KV(common-code)
 Per:IEC1000-4-5

UTP Cable Connector: 2KV(different-code),
 4KV(common-code),
 Per:IEC1000-4-5

BNC Male: 75 ohms
UTP Cable: 100 ohms
Shell: ABS
Color: Black
MTBF: >10000H
Operating Temperature: -10-55° C
Storage Temperature: -20-70° C
Humidity: 0-95%(non-condensing)

Specifications:

Transmission Signal: 1 channel

Transmission Distance:
 > HDCVI 720P: 400m/1080p:250m
 >HDTV1 720P & 1080P: 200m
 >AHD 720P: 350m/1080P:200m

Application Example:

