

STR101P-HD-E2

Features:

- >2pcs STR101P-HD-E2
- >No power required, simplified project wiring
- >Compatible with HDCV1/ HDTV1/ AHD
- >Transmission distance (over Cat 5E/6):
  - HDCV1 720P/400m; 1080P/250m
  - HDTV1 720P&1080P/250m
  - AHD 720P/350m; 1080P/200m
- >Plug and play, real-time transmit CCTV HD video signal, video is high quality and stable
- >Anti-interference, super lightning protection, ESD
- >ABS outer shell, convenient to use in intensive project
- >Screw terminal with pigtail

Advantages:

- >Screw termina
- >Economical type

Specifications:

Transmission Signal: 1 channel

- Transmission Distance:
- > HDCVI 720P: 400m/1080p:250m
  - >HDTV1 720P & 1080P: 200m
  - >AHD 720P: 350m/1080P:200m



Video Balun  
HD UTP

Specifications:

- Category Type: UTP CAT5/ 5E/ 6  
Twisted-pair Video Connector: BNC-M  
Compatible Format: HDCVI/HDTV1/AHD  
Resolution: 720P/1080P  
Ant-interference: >60db
- ESD:  
>1a contact discharge electricity level3  
>1b air discharge electricity level3  
>Per: IEC61000-4-2
- Coaxial Cable Connector: 2KV(common-code)  
Per:IEC1000-4-5  
UTP Cable Connector: 2KV(different-code),  
4KV(common-code),  
Per:IEC1000-4-5
- BNC Male: 75 ohms  
UTP Cable: 100 ohms  
Shell: ABS  
Color: Black  
MTBF: >10000H  
Operating Temperature: -10-55° C  
Storage Temperature: -20-70° C  
Humidity: 0-95%(non-condensing)

Application Example:

