

HD UTP Video Balun

STR101P-HD-S2 (4MP)

Features:

- > 2pcs STR101P-HD-S2(4MP)
- > No power required, simplified project wiring
- > Compatible with HDCVI/ HDTV1/ AHD
- > Transmission distance (over Cat 5E/6):
 - > HDCVI 720P/400m; 1080P/250m;
 - Cat 5E: 4MP(2560*1440@25): 150m
- > HDTV1 720P&1080P/250m;
- Cat 5E: 4MP(2560*1440@25): 150m
- > AHD 720P/350m; 1080P/200m
- > Plug and play, real-time transmit CCTV HD video signal, video is high quality and stable
- > Anti-interference, super lightning protection, ESD
- > ABS outer shell, convenient to use in intensive project
- > Upside push-terminal, easier for installation
- > With connecting slot, many baluns can connect together

Advantages:

- > Many baluns can be connected
- > With upside push-terminal, easier for installation

Specifications:

Transmission Signal: 1 channel

Transmission Distance:

- > HDCVI 720P: 400m/1080p:250m;
- Cat 5E: 4MP(2560*1440@25): 150m
- > HDTV1 720P & 1080P: 200m;
- Cat 5E: 4MP(2560*1440@25): 150m
- > AHD 720P: 350m/1080P:200m



Video Balun

HD UTP

Specifications:

- Category Type:** UTP CAT5/ 5E/ 6
- Twisted-pair Video Connector:** BNC-M
- Compatible Format:** HDCVI/HDTV1/AHD
- Resolution:** 720P/1080P/4MP
- Ant-interference:** >60db

ESD:

- > 1a contact discharge electricity level3
- > 1b air discharge electricity level3
- > Per: IEC61000-4-2

Coaxial Cable Connector: 2KV(common-code)
Per:IEC1000-4-5

UTP Cable Connector: 2KV(different-code),
4KV(common-code),
Per:IEC1000-4-5

BNC Male: 75 ohms

UTP Cable: 100 ohms

Shell: ABS

Color: Black

MTBF: >10000H

Operating Temperature: -10-55° C

Storage Temperature: -20-70° C

Humidity: 0-95%(non-condensing)

Typical Application:

