

STR6010-8P-125

The S5009-8P, an unmanaged Fast-Ethernet switch, is designed for residential building in the corridor-level broadband switching equipment, for the edge of the access and LAN to provide high-quality network connections. The S5009-8P provides 10 10/100Base-TX ports. It provides 8 PoE Injector.

Features:

- > Conforms to IEEE802.3, IEEE 802.3u, IEEE 802.3z, IEEE802.3af, IEEE802.3at
- > Provides 9 10/100Base-TX ports
- > Provides 8 PoE injector and 130W power adapter
- > High back-plane bandwidth 2Gbps
- > IEEE802.3x Flow control
- > Surge protection for power port and data ports
- > EMI standards complies with FCC, CE class B

Specifications:

Fixed port: 8 10/100Base-TX ports.

LED Indicators: PWR, PoE, Link/Act LED.

Input voltage: 100V~240V AC, 50/60Hz (for power adapter)
48VDC (for PoE switch)

Power consumption: 130W(125W for PoE)

Operating temperature: 0°C~40°C.



9 RJ-45 10/100M ports with 8 POE Ports Switch

with power adapter

Specifications:

Storage temperature: -10°C~70°C.

Relative humidity: 20%~89% (non-condensing).

Thermal methods: Fanless.

Switching capacity: 1.8G.

MAC address table: 4K.

Traffic control: IEEE 802.3x full-duplex flow control.

PoE port: 10 10/100Base-TX ports.

PoE Standard: IEEE802.3af, IEEE802.3at, per port 30W(MAX)
Total 130W.

Pin assignment: V+ (RJ45 Pin3,6), V- (RJ45 Pin 1,2).

Application Example:

