

STR6018-16P-250

The S6018-16P, an unmanaged Fast-Ethernet switch, is designed for residential building in the corridor-level broadband switching equipment, for the edge of the access and LAN to provide high-quality network connections. The S6018-16P provides 16 10/100Base-TX ports and 2 Gigabit Combo, It provides 16 PoE Injector.

Features:

- > Conforms to IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at
- > Provides 16 10/100Base-TX ports, 2 Gigabit Combo
- > Provides 16 PoE injector and 250W power adapter
- > High back-plane bandwidth 5.6Gbps
- > IEEE802.3x Flow control
- > Surge protection for power port and data ports



with power adapter

16 RJ-45 10/100M+2 Gigabit Combo ports with 16 POE Ports Switch

Specifications:

Storage temperature: -10℃~70℃.
Relative humidity: 20%~89% (non-condensing).

Thermal methods: Fan.

Switching capacity: 7.2G.

MAC address table: 4K.

Traffic control: IEEE 802.3x full-duplex flow control.

Size: 440x44x200mm

PoE port: 16 10/100Base-TX ports.

PoE Standard: IEEE802.3af, IEEE802.3at, per port 30W(MAX)
Total 250W.

Pin assignment: V+ (RJ45 Pin1,2), V- (RJ45 Pin 3,6).

Specifications:

Fixed port: 16 10/100Base-TX ports, 2 Combo Gigabit.

LED Indicators: PWR, PoE, Link/Act LED.

Input voltage: 100V~240V AC, 50/60Hz (for power adapter)

Power consumption: 250W(250W for PoE)

Operating temperature: 0℃~40℃.

Application Example:

