

STR7026-24P-250

The S7026-24P, an unmanaged Gigabit-Ethernet switch, is designed for residential building in the corridor-level broadband switching equipment, for the edge of the access and LAN to provide high-quality network connections. The S7026-24P provides 24 10/100/1000Base-TX ports and 2 Gigabit SFP, It provides 24 PoE Injector.

Features:

- > Conforms to IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at
- > Provides 24 10/100Base-TX ports, 2 Gigabit Combo
- > Provides 24 PoE injector and Built-in power supply
- > High back-plane bandwidth 52Gbps
- > IEEE802.3x Flow control
- > Surge protection for power port and data ports



STR7026-24P-250

Specifications:

Fixed port: 24 10/100/1000Base-TX ports, 2 Combo Gigabit.

LED Indicators: PWR, PoE, Link/Act LED.

Input voltage: 100V~240V AC, 50/60Hz

Power consumption: 370W&250W(for PoE)

Operating temperature: 0°C~40°C.

Specifications:

Storage temperature: -10°C~70°C.

Relative humidity: 20%~89% (non-condensing).

Thermal methods: Built-in fan.

Switching capacity: 52G.

MAC address table: 8K.

Traffic control: IEEE 802.3x full-duplex flow control.

Size: 440x44x200mm(1U)

PoE port: 24 10/100/1000Base-TX ports.

PoE Standard: IEEE802.3af, IEEE802.3at, per port 30W(MAX)
Total 250W.

Pin assignment: V+ (RJ45 Pin1,2), V- (RJ45 Pin 3,6).

Application Example:

